



Unit : mm

Model	Tube φD.	R	A	B	L	φP	C	E	Hex. H	Weight (g)	Orifice dia. (φmm)	Eff. sect. Area (mm <sup>2</sup> )	CAD file No.
PPL4-M5SUS□□	4	M5×0.8	2.9	20.3	22.4	10	14.9	18	10	7	1.8	1.5	TFPP-012
PPL4-01SUS□□		R1/8	8	23.3	24.3					10			
PPL4-02SUS□□		R1/4	11	26.3	25.3					14	18.5		
PPL6-M5SUS□□	6	M5×0.8	2.9	22	25.4	12.5	16.8	19.8	12	11	1.8	1.5	
PPL6-01SUS□□		R1/8	8	25	27.3					12.5			
PPL6-02SUS□□		R1/4	11	28	28.3					14	20		
PPL8-01SUS□□	8	R1/8	8	28	31.3	14.5	18.2	22.7	14	16	6	16.5	
PPL8-02SUS□□		R1/4	11	31	32.3					21.5			
PPL10-02SUS□□	10	R1/4	11	36	38.8	17.5	20.2	26.2	17	30.5	8	30	
PPL10-03SUS□□		R3/8	12	37	39.5					38			
PPL12-03SUS□□	12	R3/8	12	39	43.2	21	23.4	29.4	21	45.5	10	47	
PPL12-04SUS□□		R1/2	15	42	44.5					60			

\*1. L dimension is a reference dimension after tightening screw.

\*2. Please enter C in the □ of model code only when Clean room specification is required.

\*3. Please enter S in the □ of model code when Sealock treated on screw is required.